NSN 5905-00-476-6213

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-476-6213 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.6240 inches and 0.6250 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 0.625 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.024 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.688 inches **Body Length:** 3.900 inches **Mounting Lip Diameter:** Between 0.8650 inches and 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.40 inch-ounces **Shaft End Play:** 0.005 inches

Shaft Runout: 0.002 inches



NSN 5905-00-476-6213 Precision Wire Wound Variable Resistor - Page 2 of 3	Aero
Lateral Runout:	
0.004 inches	
Pilot Diameter Runout:	
0.00200 inches	
Shaft Radial Play:	
0.002 inches	
Mechanical Backlash In Deg Angular Rotation:	
4.5	
Terminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
Clamp ring	
Electrical Resistance Per Section:	
10.0 kilohms single section	
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:	
1800.0 single section	
Rotary Actuator Travel In Angular Deg:	
3600.0	
Function Conformity Tolerance Per Section:	
-0.20/+0.20 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
125.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
-20.0/+20.0 single section	
Power Dissipation Rating Per Section In Watts:	
2.0 free air single section	
Function Conformity Per Section:	

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Tap Location Tolerance Per Section:

-1.0/+1.0 degrees angular rotation single section

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Actuator Travel Control Feature:

Clutch

Function Characteristic Per Section:

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

NSN 5905-00-476-6213

Precision Wire Wound Variable Resistor - Page 3 of 3



			ure:	

--

Demilitarization:

No

Fiig:

A002a0