

View Online at <https://aerobasegroup.com/nsn/5905-00-476-6676>

Section Quantity:

1

Overall Length:

2.980 inches

First Flat Length:

0.440 inches

Flat Height:

0.218 inches

Shaft Diameter:

0.249 inches

Shaft Length:

0.880 inches

Overall Diameter:

1.880 inches

Shaft Style:

Round, flatted

Switch Type:

Rotary

Switch Voltage Rating In Volts:

125.0

Contact Arm Electrical Off Position:

Fully cw

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

250.0

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.500 inches

Switch Operating Position:

End of rotation

Switch Contact Arrangement:

Single pole, double throw, three positions maintained

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

50.000 ohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Power Dissipation Rating Per Section In Watts:

25.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Switch Current Type And Rating In Amps:

5.000 ac/dc

Test Data Document:

97499-209-075-607 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 eyelet and 1 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A002a0