NSN 5905-00-477-1612

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-477-1612

-20.0/+20.0 Electrical Resistance: 5.000 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:
5.000 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0
Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0
50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Tomparatare range or remparatare occurrent in Dog ocionae.
-55.0/+275.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reliability Indicator:
Not established
Body Diameter:
0.094 inches
Body Length:
0.562 inches
Power Dissipation Rating In Watts:
1.000 free air
Style Designator:
Axial terminal each end
Test Data Document:
97424-6146k70 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0