## NSN 5905-00-477-2135

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-477-2135 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.470 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.600 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.125 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 180.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:** 

Humidity proof

**Electrical Resistance Per Section:** 

70.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

180.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section

## NSN 5905-00-477-2135

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolera	nce Per	Section	n Percent:
4.044.0-:	-4:		

-1.0 to 1.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A002a0