NSN 5905-00-477-2363

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-477-2363 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.812 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.500 inches **Shaft Bearing Type:** Sleeve **Actuator Type:** Integral knob **Nonturn Device Location:** At 12 oclock **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 42.0 ohms single section **Power Dissipation Rating Per Section In Watts:** 25.0 free air single section **Resistance Tolerance Per Section In Percent:** -7.1 to 7.1 single section **Criticality Code Justification:** Feat **Standard Taper Curve Per Section:** A single section **Special Features:** Flight critical of the h-2 aircraft **Terminal Type And Quantity:**

2 tab w/screw

NSN 5905-00-477-2363

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0