## NSN 5905-00-477-4449

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-477-4449 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.188 inches **Body Diameter:** 0.938 inches **Body Length:** 0.688 inches **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 265.0 **Maximum Running Torque:** 5.00 inch-ounces **Maximum Stop Torque:** 160.00 inch-ounces **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi):

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Shaft and standard bushing

**Features Provided:** 

Panel seal

32.0

**Electrical Resistance Per Section:** 

500.0 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

285.0

**Power Dissipation Rating Per Section In Watts:** 

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

**Actuator Travel Control Feature:** 

Stops

## NSN 5905-00-477-4449

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig: A002a0