

View Online at <https://aerobasegroup.com/nsn/5905-00-477-5142>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.875 inches

Shaft Diameter:

Between 0.263 inches and 0.265 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.312 inches

Body Length:

1.875 inches

Undercut Diameter:

Between 0.185 inches and 0.187 inches

Shaft Style:

Round, stepped

Switch Type:

Push-pull

Switch Voltage Rating In Volts:

125.0

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

290.0

Switch Operating Position:

Any position of rotation travel

Switch Contact Arrangement:

Double pole, double throw

Undercut Length:

0.437 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

10.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

290.0

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Terminal Type And Quantity:

9 eyelet

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0