Nonprecision Wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-00-477-8132



Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Thread Length:

0.380 inches

Mounting Hole Diameter:

Between 0.086 inches and 0.093 inches

Shaft Diameter:

0.086 inches

Shaft Length:

0.500 inches

Body Length:

1.265 inches

Body Width:

0.295 inches

Body Height:

0.325 inches

Shaft Style:

Round, threaded

Actuator Type:

Single shaft

Longitudinal Actuator Travel:

0.437 inches

Longitudinal Actuator Effective Electrical Stroke Length:

0.407 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

5.0 kilohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Power Dissipation Rating Per Section In Watts:

0.8 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section



Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0