NSN 5905-00-477-8253

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-477-8	253
Section Quantity:	
2	
Body Style:	
Cylindrical servo mounted	
Reliability Indicator:	
Not established	
Pilot Diameter:	
0.7500 inches	
Pilot Length:	
0.0620 inches	
Overall Length:	
2.042 inches	
Undercut Diameter:	
0.781 inches	
Undercut Width:	
0.0620 inches	
Body Diameter:	
0.970 inches	
Shaft Diameter:	
Between 0.2496 inches and 0.2498 inches	
Shaft Length:	
0.792 inches	
Body Length:	
1.250 inches	
Overall Diameter:	
1.079 inches	
Mounting Lip Diameter:	
0.8750 inches	
Mounting Lip Depth:	
0.0620 inches	
Shaft Style:	
Round	
Shaft Bearing Type:	
Ball	
Actuator Type:	
Single shaft	
Effective Electrical Rotation In Deg Angular Rotation:	
348.0	
Maximum Starting Torque:	
9 00 inch gunges	

8.00 inch-ounces

Maximum Running Torque:

8.00 inch-ounces

NSN 5905-00-477-8253

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.002 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.00100 inches
Shaft Radial Play:
0.003 inches
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
1.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
350.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 all sections
Power Dissipation Rating Per Section In Watts:
2.5 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
1 all sections
Tap Location Tolerance Per Section:
-1.0/+1.0 ohms all sections
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Stops
Tap Location From Ccw Terminal Per Section In Ohms:
500.0 all sections
Function Characteristic Per Section:
All sections linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 all sections

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

NSN 5905-00-477-8253

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
8 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0