## NSN 5905-00-478-1274

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-478-1274 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.813 inches **Mounting Bushing Length:** 0.313 inches **Body Length:** 0.750 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Contact Arm Electrical Off Position:** Fully cw **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Stop Torque:** 0.50 inch-ounces **Nonturn Device Location:** At 3 oclock **Nonturn Device Radius:** 0.490 inches **Shaft End Play:** 0.002 inches **Shaft Runout:** 

0.002 inches

Lateral Runout:
0.002 inches

Pilot Diameter Runout:
0.00150 inches

## NSN 5905-00-478-1274

Precision Wire Wound Variable Resistor - Page 2 of 3



| Shaft Radial Play:   |
|--|
| 0.002 inches   |
| Fragility Factor:  |
| Rugged   |
| Screw Thread Diameter:   |
| 0.375 inches   |
| Screw Thread Series Designator:  |
| Unef   |
| Screw Thready Qty Per Inch (tpi):  |
| 32.0   |
| Terminal Location:   |
| Longitudinally positioned on the circumference                                 |
| Mounting Method:   |
| Standard bushing   |
| Electrical Resistance Per Section:   |
| 5.0 kilohms single section   |
| Rotary Actuator Travel In Angular Deg:   |
| 3600.0   |
| Function Conformity Tolerance Per Section:                                     |
| -0.25/+0.25 single section   |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:    |
| 125.0 single section   |
| Power Dissipation Rating Per Section In Watts:                                 |
| 2.0 free air single section  |
| Function Conformity Per Section:   |
| Single section independent linearity   |
| Resistance Tolerance Per Section In Percent:                                   |
| -5.0/+5.0 single section   |
| Actuator Travel Control Feature:   |
| Stops  |
| Function Characteristic Per Section:   |
| Single section linear  |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: |
| -20.0/+20.0 single section   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:            |
| 40.0 single section  |
| Terminal Type And Quantity:  |
| 3 tab, solder lug  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |

No

## NSN 5905-00-478-1274

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0