## NSN 5905-00-478-5150

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-478-5150

Section Quantity:						
1						
Shaft Diameter:						
Between 0.2494 inches and 0.2497 inches						
Shaft Length:						
0.813 inches						
Mounting Bushing Length:						
0.313 inches						
Shaft Style:						
Round, slotted						
Actuator Type:						
Single shaft						
Effective Electrical Rotation In Deg Angular Rotation:						
1800.0						
Maximum Starting Torque:						
0.60 inch-ounces						
Maximum Running Torque:						
0.60 inch-ounces						
Maximum Stop Torque:						
48.00 inch-ounces						
Shaft End Play:						
0.00500 inches						
Shaft Runout:						
0.002 inches						
Shaft Radial Play:						
0.002 inches						
Screw Thread Diameter:						
0.375 inches						
Screw Thread Series Designator:						
Unef						
Screw Thready Qty Per Inch (tpi):						
32.0						
Mounting Method:						
Standard bushing						
Electrical Resistance Per Section:						
120.000 ohms single section						
Rotary Actuator Travel In Angular Deg:						
1800.0						
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:						
125.0 single section						
Power Dissipation Rating Per Section In Watts:						
4. Figure air air air agus agustian						

1.5 free air single section

## NSN 5905-00-478-5150

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



R	esistance	<b>Tolerance</b>	Per 9	Section	In	Percent:
◥	esisiance	i olei alice	rei .	Section		reiteiit.

-3.0 to 3.0 single section

**Actuator Travel Control Feature:** 

Continuous motion

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0