Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-478-6386

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

#### **Overall Length:**

2.812 inches

#### **Body Diameter:**

1.812 inches

#### Shaft Diameter:

0.2497 inches

#### Shaft Length:

0.812 inches

#### Mounting Bushing Length:

## 0.312 inches

**Body Length:** 

2.000 inches

#### **Overall Diameter:**

2.140 inches

#### Shaft Style:

Round

#### Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

3600.0

#### Maximum Starting Torque:

3.00 inch-ounces

#### Nonturn Device Location:

At 12 oclock

#### **Nonturn Device Radius:**

0.562 inches

#### Shaft End Play:

0.00500 inches

#### Shaft Runout:

0.0005 inches

### Lateral Runout:

0.003 inches

### **Pilot Diameter Runout:**

0.00200 inches



# Shaft Radial Play: 0.003 inches Screw Thread Diameter: 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 100.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.25/+0.25 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 5.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -1.0/+1.0 single section **Actuator Travel Control Feature:** Stops **Criticality Code Justification:** Zzzy **Function Characteristic Per Section:** Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Terminal Type And Quantity:** 3 tab, solder lug **Reference Number Differentiating Characteristics:** Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a

#### Unit Of Measure:

# NSN 5905-00-478-6386

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0