NSN 5905-00-478-7189

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-478-7189 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 0.555 inches **Terminal Length:** 0.500 inches **Overall Height:** 0.500 inches **Overall Width:** 0.220 inches **Mounting Hole Diameter:** 0.078 inches **Shaft Diameter:** 0.078 inches **Shaft Length:** 0.045 inches **Body Length:** 0.500 inches **Body Width:** 0.220 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Center To Center Distance Between Terminals:** 0.200 inches **Lateral Distance Between Mounting Hole Centers:** 0.520 inches **Mounting Facility Quantity:**

2
Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal and unthreaded hole

NSN 5905-00-478-7189

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Features Provided:
Humidity proof
Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A002a0