NSN 5905-00-478-7194

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-478-7194 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.261 inches **Body Diameter:** 1.156 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.995 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.266 inches **Overall Diameter:** 1.750 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 309.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches Radially positioned over less than half the circumference

Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location: Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 500.0 kilohms all sections

NSN 5905-00-478-7194

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:	
320.0	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
120.0 all sections	
Power Dissipation Rating Per Section In Watts:	
2.0 free air all sections	
Resistance Tolerance Per Section In Percent:	
-10.0/+10.0 all sections	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 all sections	
Terminal Type And Quantity:	
6 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A002a0	