NSN 5905-00-479-3800

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-479-3800 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.625 inches First Flat Length: 0.625 inches Flat Height: Between 0.214 inches and 0.218 inches **Body Diameter:** 1.156 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** 2.000 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.625 inches **Overall Diameter:** 1.156 inches **Shaft Style:** Round, flatted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 192.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.526 inches and 0.536 inches

NSN 5905-00-479-3800 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mechanical Backlash In Deg Angular Rotation:
1.5
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Jnef Control of the C
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
312.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0 to 5.5 -55 degrees celsius single section and +0.0 to 3.0 -25 degrees celsius single section and +0.0 to 1.5 0 degrees celsius single
section and -2.0 to 2.0 85 degrees celsius single section and +0.0 to 4.5 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.25 free air single section
Resistance Tolerance Per Section In Percent:
10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0