

View Online at <https://aerobasegroup.com/nsn/5905-00-479-9639>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting holes

**Overall Length:**

0.560 inches

**Terminal Length:**

0.380 inches

**Overall Height:**

0.500 inches

**Overall Width:**

0.580 inches

**Mounting Hole Diameter:**

0.080 inches

**Shaft Diameter:**

0.078 inches

**Shaft Length:**

0.060 inches

**Body Length:**

0.500 inches

**Body Width:**

0.200 inches

**Body Height:**

0.500 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Single shaft

**Mechanical Backlash In Deg Angular Rotation:**

0.5

**Center To Center Distance Between Terminals:**

0.200 inches

**Lateral Distance Between Mounting Hole Centers:**

0.520 inches

**Mounting Facility Quantity:**

2

**Center To Center Distance Between Terminal Rows:**

0.100 inches

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

500.000 ohms single section

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.100 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-100.0 to 100.0 single section

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Standard Taper Curve Per Section:**

A single section

**Test Data Document:**

94756-444-0218 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0