NSN 5905-00-480-1730

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-480-1730

-5.0/+5.0 Electrical Resistance: 5.690 kilohms Resistance Tolerance in Percent: -0.250/+0.250 Ambient Tempurature in Deg Celsius At Full Rated Power: 6.0.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -5.50/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: -0.295 inches Body Width: -0.395 inches Body Width: -0.300 free air Sylve Designator: Terminals one edge Tost Data Document: 93/44-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Na Unit of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
8. Resistance Tolerance in Percent: -0.250/40.250 Ambient Tempurature In Deg Celsius At Full Rated Power: 60.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminal Sysyle Designator: Terminal Sysyle Designator: Terminal Sysyle Designation; standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) No Unit Of Measure:	-5.0/+5.0
Resistance Tolerance In Percent: -0.250/+0.250 Ambient Tempurature In Deg Celsius At Full Rated Power: 6.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure:	Electrical Resistance:
-0.250/+0.250 Ambient Tempurature In Deg Celsius At Full Rated Power: 60.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.320 inches Body Width: 0.320 inches Body Width: 0.320 inches Sody Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	5.690 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 60.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.320 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Wieth: 0.320 inches Body Wieth: 0.300 inches Power Dissipation Rating in Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	-0.250/+0.250
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Weight: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	60.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-56.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating in Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	175.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating in Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-55.0/+125.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Reliability Indicator:
0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.295 inches
Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Width:
O.100 inches Power Dissipation Rating In Watts: O.300 free air Style Designator: Terminals one edge Test Data Document: O9344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.320 inches
Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Height:
O.300 free air Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.100 inches
Style Designator: Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Terminals one edge Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.300 free air
Test Data Document: 09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminals one edge
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	09344-ps7044 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0