Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-480-3997

Section	Quantity:

1

Body Style:

Cylindrical

**Reliability Indicator:** 

Not established

**Overall Length:** 

0.766 inches

Terminal Length:

0.375 inches

Body Diameter:

0.375 inches

Body Length:

#### 0.375 inches

**Overall Diameter:** 

0.375 inches

Actuator Type:

Flush drive with slot-hole

## Effective Electrical Rotation In Deg Angular Rotation:

280.0

### Center To Center Distance Between Terminals:

0.200 inches

#### **Terminal Location:**

Rear end

### **Mounting Method:**

Terminal

### **Electrical Resistance Per Section:**

20.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

280.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0 to 250.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## Actuator Travel Control Feature:

Stops



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0