NSN 5905-00-480-5238

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-480-5238

Section Quantity:
1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.100
Overall Length:
0.555 inches
Terminal Length:
0.172 inches
Overall Height:
0.500 inches
Overall Width:
0.372 inches
Mounting Hole Diameter:
0.073 inches
Shaft Diameter:
0.078 inches
Shaft Length:
0.045 inches
Body Length:
0.500 inches
Body Width:
0.235 inches
Body Height:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 7200.0 and 15120.0
Maximum Starting Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Lateral Distance Between Mounting Hole Centers:
0.520 inches

Mounting Facility Quantity:

NSN 5905-00-480-5238

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Left adjacent side two rows
Mounting Method:
Unthreaded hole
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
200.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 7200.0 and 15120.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-39015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 pin
Specification Data:
81349-mil-r-39015/2 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: