NSN 5905-00-481-5737

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-481-5737 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.3120 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.375 inches **Undercut Width:** 0.0930 inches **Body Diameter:** 1.437 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Body Length:** 1.499 inches **Mounting Lip Diameter:** 1.4370 inches **Mounting Lip Depth:** 0.0730 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.40 inch-ounces **Shaft End Play:** 0.0025 inches

Shaft Runout: 0.001 inches

NSN 5905-00-481-5737

Precision Wire Wound Variable Resistor - Page 2 of 3



Pilot Diameter Runout:
0.003 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
20.0 kilohms all sections
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
180.0 all sections
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 all sections
Power Dissipation Rating Per Section In Watts:
2.0 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
2 all sections
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation all sections
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Test Data Document:
91417-118205 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
8 turret
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5905-00-481-5737

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0