## NSN 5905-00-481-7335

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-481-7335

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Overall Length:
0.515 inches
Terminal Length:
0.156 inches
Body Diameter:
0.687 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.187 inches
Body Length:
0.328 inches
Overall Diameter:
0.906 inches
Shaft Style:
Round, slotted
Switch Type:
Rotary
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
280.0
Maximum Starting Torque:
2.00 inch-ounces
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
0.312 inches
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally closed
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Terminal
Electrical Resistance Per Section:

1.000 megohms single section

## NSN 5905-00-481-7335

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:	
315.0	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
85.0 single section	
Power Dissipation Rating Per Section In Watts:	
0.1 free air single section	
Resistance Tolerance Per Section In Percent:	
-10.0 to 10.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
55.0 single section	
Standard Taper Curve Per Section:	
A single section	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Filig:	
A002a0	