

View Online at https://aerobasegroup.com/nsn/5905-00-481-7808

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-10.0/+10.0

## **Electrical Resistance:**

2.490 kilohms

# **Resistance Tolerance In Percent:**

-0.050/+0.050

## Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

# Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

145.0

# Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-65.0/+145.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Type:**

Wire lead

# \_ .. . ..... .. ..

Reliability Indicator:

# Established

**Reliability Failure Rate Level In Percent:** 

0.010

# **Terminal Length:**

1.500 inches

#### Body Diameter:

0.250 inches

## Body Length:

0.500 inches

# **Power Dissipation Rating In Watts:**

0.150 free air

# **Unpackaged Unit Weight:**

2.000 grams

# Style Designator:

Axial terminal each end

# Test Data Document:

81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-r-39005/4 government specification

# Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

# NSN 5905-00-481-7808

Noninductive Wire Wound Fixed Resistor - Page 2 of 2

Fiig: A001a0

