NSN 5905-00-481-8130

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-481-8130

-500.01+500.0 -500.01+500.0 -500.01+500.0 -500.01+500.0 -500.00+500.0	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: -10.000/+10.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+450.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.380 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating in Watts: 125.000 free air Style Designator: Avail terminal each end Test Data Document: 14304-90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	
Resistance Tolerance In Percent: -10.000/+10.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+450.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.880 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 155.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-P0-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure:	Electrical Resistance:
-10.000/+10.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 300.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+450.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.880 inches Body Diameter: 1.000 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	100.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 355.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4450.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.880 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+450.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.880 inches Body Diameter: 1.000 inches Body Diameter: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-190-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	-10.000/+10.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+450.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.880 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-190-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.014-450.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.880 inches Body Diameter: 1.000 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-790-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	40.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+450.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.880 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 114304-190-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0/+450.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.880 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-790-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Flig:	350.0
Inclosure Method: Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.880 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-190-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.880 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-190-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-55.0/+450.0
Terrinal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.880 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-190-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Inclosure Method:
Ferrule Reliability Indicator: Not established Terminal Length: 0.880 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Terminal Length: 0.880 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note stablished Terminal Length: 0.880 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Ferrule
Terminal Length: 0.880 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Reliability Indicator:
0.880 inches Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Diameter: 1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Length:
1.000 inches Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.880 inches
Body Length: 6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
6.240 inches Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1.000 inches
Power Dissipation Rating In Watts: 125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
125.000 free air Style Designator: Axial terminal each end Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	6.240 inches
Style Designator: Axial terminal each end Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	125.000 free air
Test Data Document: 14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	14304-r90-0003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0