

View Online at <https://aerobasegroup.com/nsn/5905-00-481-8478>

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

Between 0.285 inches and 0.315 inches

Shaft Diameter:

Between 0.080 inches and 0.100 inches

Shaft Length:

Between 0.030 inches and 0.050 inches

Body Length:

Between 0.360 inches and 0.390 inches

Body Width:

Between 0.188 inches and 0.218 inches

Body Height:

Between 0.360 inches and 0.390 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9000.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

Between 0.190 inches and 0.210 inches

Fragility Factor:

Moderately rugged

Terminal Location:

Left adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

Between 0.090 inches and 0.110 inches

Features Provided:

Humidity proof

Cubic Measure:

0.033 cubic inches

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.090 inches and 0.110 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Test Data Document:

97871-352-0089-001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0