Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-482-0620

## Section Quantity:

1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.344 inches Flat Height: Between 0.211 inches and 0.221 inches **Body Diameter:** 1.680 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 1.203 inches and 1.297 inches Mounting Bushing Length: 0.375 inches **Body Length:** 1.410 inches Shaft Style: Round, flatted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: Between 275.0 and 305.0 **Nonturn Device Location:** At 12 oclock

**Nonturn Device Radius:** 

Between 0.485 inches and 0.515 inches

#### **Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** 

Locking bushing

**Electrical Resistance Per Section:** 

300.0 ohms single section

# NSN 5905-00-482-0620 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

AeroBase Group

**Rotary Actuator Travel In Angular Deg:** 

Between 275.0 and 305.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

Power Dissipation Rating Per Section In Watts:

25.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

#### **Test Data Document:**

81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

3 tab, solder lug

Specification Data:

81349-mil-r-22/3 government specification

Shelf Life:

N/a

#### Unit Of Measure:

--

#### **Demilitarization:**

No

Fiig:

A002a0