Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-482-3329

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.875 inches

#### Shaft Diameter:

0.125 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.250 inches

#### Body Length:

#### 0.688 inches

Shaft Style:

Round

### Actuator Type:

Single shaft

## Nonturn Device Location:

At 6 oclock

## Nonturn Device Radius:

0.250 inches

### Screw Thread Diameter:

0.250 inches

#### **Screw Thread Series Designator:**

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Standard bushing

# **Electrical Resistance Per Section:**

10.0 ohms single section

# Rotary Actuator Travel In Angular Deg:

300.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

# Power Dissipation Rating Per Section In Watts:

12.5 free air single section



### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

#### Actuator Travel Control Feature:

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0