

View Online at <https://aerobasegroup.com/nsn/5905-00-482-4076>

Section Quantity:

4

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.31200 inches and 1.31250 inches

Pilot Length:

0.06200 inches

Undercut Diameter:

1.313 inches

Undercut Width:

0.07300 inches

Body Diameter:

1.440 inches

Shaft Diameter:

0.249 inches

Shaft Length:

0.680 inches

Body Length:

2.300 inches

Mounting Lip Diameter:

1.43700 inches

Mounting Lip Depth:

0.09300 inches

Shaft Style:

Round, slotted

Actuator Type:

Double ended shaft

Maximum Starting Torque:

4.00 inch-ounces

Maximum Running Torque:

3.00 inch-ounces

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

10.000 percent, rated amperes c and better v.G. Stepping

Rotary Actuator Travel In Angular Deg:

340.0

Function Conformity Tolerance Per Section:

-5.00/+5.00 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Function Conformity Per Section:

All sections absolute linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0