## NSN 5905-00-482-5031

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-482-5031 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 4.375 inches **Terminal Length:** 0.375 inches **Body Diameter:** 3.312 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 1.500 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 2.875 inches **Overall Diameter:** 3.687 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 5400.0 **Maximum Starting Torque:** 2.70 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Shaft End Play:** 0.007 inches

Shaft Runout: 0.0005 inches

## NSN 5905-00-482-5031

Precision Wire Wound Variable Resistor - Page 2 of 3



Lateral Runout:
0.003 inches
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.500 inches
Screw Thread Series Designator:
Uns
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
5400.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
10.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5905-00-482-5031

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0