NSN 5905-00-482-5293

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-482-5293 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.128 inches **Body Diameter:** 0.850 inches **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** 0.680 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.448 inches **Overall Diameter:** 1.250 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.40 inch-ounces

Maximum Stop Torque: 160.00 inch-ounces **Shaft End Play:** 0.010 inches **Shaft Runout:** 0.001 inches **Lateral Runout:** 0.002 inches **Pilot Diameter Runout:** 0.003 inches

NSN 5905-00-482-5293

Precision Wire Wound Variable Resistor - Page 2 of 3



| Shaft Radial Play: |
|-----------------------------------------------------------------------------|
| 0.002 inches |
| Screw Thread Diameter: |
| 0.250 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Longitudinally positioned on the circumference |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 2.5 percent, rated amperes c and better flooring |
| Rotary Actuator Travel In Angular Deg: |
| 3600.0 |
| Function Conformity Tolerance Per Section: |
| -0.25/+0.25 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -11.0/+11.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 5.0 7th secondary quality |
| Function Conformity Per Section: |
| Single section zero based linearity |
| Resistance Tolerance Per Section In Percent: |
| -3.0/+3.0 single section |
| Actuator Travel Control Feature: |
| Clutch |
| Function Characteristic Per Section: |
| 7 oclock all primaries |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 40.0 single section |
| Precious Material And Location: |
| Terminal surface gold |
| Precious Material: |
| Gold |
| Terminal Type And Quantity: |
| 3 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

-

NSN 5905-00-482-5293

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0