

View Online at https://aerobasegroup.com/nsn/5905-00-482-5293

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.128 inches

Body Diameter:

0.850 inches

Shaft Diameter:

Between 0.1245 inches and 0.1248 inches

Shaft Length:

0.680 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.448 inches

Overall Diameter:

1.250 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.40 inch-ounces

Maximum Stop Torque:

160.00 inch-ounces

Shaft End Play:

0.010 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.003 inches



Shaft Radial Play:	
0.002 inches	
Screw Thread Diameter:	
0.250 inches	
Screw Thread Series Designator:	
Unef	
Screw Thready Qty Per Inch (tpi):	
32.0	
Terminal Location:	
Longitudinally positioned on the circumference	
Mounting Method:	
Standard bushing	
Electrical Resistance Per Section:	
2.5 percent, rated amperes c and better flooring	
Rotary Actuator Travel In Angular Deg:	
3600.0	
Function Conformity Tolerance Per Section:	
-0.25/+0.25 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
125.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
-11.0/+11.0 single section	
Power Dissipation Rating Per Section In Watts:	
5.0 7th secondary quality	
Function Conformity Per Section:	
Single section zero based linearity	
Resistance Tolerance Per Section In Percent:	
-3.0/+3.0 single section	
Actuator Travel Control Feature:	
Clutch	
Function Characteristic Per Section:	
7 oclock all primaries	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
40.0 single section	
Precious Material And Location:	
Terminal surface gold	
Precious Material:	
Gold	
Terminal Type And Quantity:	
3 turret	
Shelf Life:	
N/a	
Unit Of Measure:	



Demilitarization:

No

Fiig:

A002a0