NSN 5905-00-482-7712

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-482-7712

Tempurature Coefficient Of Resistance In Dam Der Der Coloius
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-10.0/+10.0
Electrical Resistance:
3.300 kilohms
Resistance Tolerance In Percent:
-0.100/+0.100
Ambient Tempurature In Deg Celsius At Full Rated Power:
125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
145.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-65.0/+145.0
Inclosure Method:
Encapsulated Terminal Type:
Wire lead
Reliability Indicator: Established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
1.000 inches
Body Diameter: 0.250 inches
Body Length: 0.312 inches
Power Dissipation Rating In Watts:
0.125 free air
Cubic Measure (non-core):
0.015 cubic inches
Style Designator:
Axial terminals one end
Test Data Document:
81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil39005/6 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-482-7712

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0