Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-483-3242

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Overall Length:

1.320 inches

Terminal Length:

0.500 inches

Overall Height:

0.937 inches

Overall Width:

0.328 inches

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.125 inches

Body Length:

1.250 inches

Body Width:

0.328 inches

Body Height:

0.452 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3960.0

Maximum Starting Torque:

7.50 inch-ounces

Center To Center Distance Between Terminals:

0.700 inches

Lateral Distance Between Mounting Hole Centers:

0.100 inches

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

Electrical Resistance Per Section:

2.200 kilohms single section

Rotary Actuator Travel In Angular Deg:

3960.0



Center To Center Distance Between Center Terminal And Outside Terminal: 0.300 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0