

View Online at <https://aerobasegroup.com/nsn/5905-00-483-3295>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.0290 inches and 1.0300 inches

Pilot Length:

0.0400 inches

Undercut Diameter:

Between 1.029 inches and 1.030 inches

Undercut Width:

0.0200 inches

Body Diameter:

1.090 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.750 inches

Body Length:

0.820 inches

Mounting Lip Diameter:

1.0900 inches

Mounting Lip Depth:

0.0600 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

35.0

Maximum Starting Torque:

1.00 inch-ounces

Fragility Factor:

Moderately rugged

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Humidity proof

Cubic Measure:

0.701 cubic inches

Electrical Resistance Per Section:

3.5 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Power Dissipation Rating Per Section In Watts:

0.2 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0