

View Online at <https://aerobasegroup.com/nsn/5905-00-483-4005>

**Section Quantity:**

1

**Body Style:**

Rectangular

**Reliability Indicator:**

Not established

**Terminal Length:**

0.500 inches

**Body Length:**

0.315 inches

**Body Width:**

0.500 inches

**Body Height:**

0.577 inches

**Actuator Type:**

Integral knob

**Effective Electrical Rotation In Deg Angular Rotation:**

280.0

**Center To Center Distance Between Terminals:**

0.200 inches

**End Application:**

Tarawa class lha, spruance class d (963), austin ship class lpd-4 amphibious transport docks, missile aia-to-air phoenix(aim-54), whidbey island class lsd, sirius class t-afs 8, Forrestal class cv, Oliver Perry class ffg, general purpose electronic test equipment, millille all-weather antiship harpoon(agm-84)

**Terminal Location:**

Lower adjacent side single row

**Mounting Method:**

Terminal

**Electrical Resistance Per Section:**

20.0 ohms single section

**Rotary Actuator Travel In Angular Deg:**

280.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.100 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-70.0 to 70.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Actuator Travel Control Feature:**

Stops

**Criticality Code Justification:**

Feat

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 single section

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0