NSN 5905-00-483-4593

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-483-4593

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.875 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.531 inches
Mounting Bushing Length:
0.344 inches
Body Length:
0.688 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
0.250 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing
Electrical Resistance Per Section:
10.0 ohms single section
Rotary Actuator Travel In Angular Deg:
300.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

NSN 5905-00-483-4593

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
12.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: