NSN 5905-00-484-2873

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-484-2873

Section Quantity:
1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Terminal Length:
0.187 inches
Mounting Hole Diameter:
0.073 inches
Shaft Diameter:
0.083 inches
Shaft Length:
0.080 inches
Body Length:
0.500 inches
Body Width:
0.190 inches
Body Height:
0.530 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
15120.0
Center To Center Distance Between Terminals:
0.200 inches
Lateral Distance Between Mounting Hole Centers:
0.562 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
15120.0
Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

NSN 5905-00-484-2873

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:** No