NSN 5905-00-484-2894

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-484-2894 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Overall Length:** Between 0.747 inches and 0.762 inches **Terminal Length:** Between 0.172 inches and 0.177 inches **Overall Height:** Between 0.490 inches and 0.510 inches **Overall Width:** Between 0.180 inches and 0.230 inches **Shaft Diameter:** Between 0.058 inches and 0.098 inches **Shaft Length:** Between 0.040 inches and 0.045 inches **Body Length:** Between 0.535 inches and 0.540 inches **Body Width:** Between 0.180 inches and 0.230 inches **Body Height:** Between 0.490 inches and 0.510 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 7200.0 and 16200.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces

Center To Center Distance Between Terminals: Between 0.195 inches and 0.205 inches **Terminal Location:**

Rear end

Mounting Method:

Terminal

NSN 5905-00-484-2894

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 7200.0 and 16200.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.095 inches and 0.105 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0 to 250.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 pin
Specification Data:
81349-mil-r-22097/3 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No