Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-484-2972

## Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

#### **Overall Length:**

0.810 inches

#### Terminal Length:

0.280 inches

#### **Overall Height:**

0.560 inches

#### **Overall Width:**

0.280 inches

#### Body Length:

### 0.750 inches

# Body Width:

0.280 inches

# Body Height:

0.190 inches

#### Actuator Type:

Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

5400.0

#### Maximum Starting Torque:

8.00 inch-ounces

#### Center To Center Distance Between Terminals:

0.500 inches

#### **Terminal Location:**

Lower adjacent side single row

#### **Mounting Method:**

Terminal

#### **Features Provided:**

Humidity proof

#### **Electrical Resistance Per Section:**

50.0 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

5400.0

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.200 inches

# Power Dissipation Rating Per Section In Watts:

0.75 free air single section



**Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Terminal Type And Quantity: 3 pin Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0