NSN 5905-00-484-4568

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-484-4568

-200.0/+200.0 Electrical Resistance: 13.000 kilohms Resistance Tolerance in Percent: -2.000/+2.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.248 inches Body Length: 0.568 inches Power Dissipation Rating in Watts: 1.0000 free air Style Dasignator: Avial terminal each end Test Data Document: 81205-bacth14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shef Lite: N/a Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -2.0004-2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 15.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.248 inches Body Length: 0.568 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: At lat terminal each end Test Data Document: 81205-bacch14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). She't Life: N/a Unit Of Measure:	-200.0/+200.0
Resistance Tolerance in Percent: -2.000/+2.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+ 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.248 inches Body Length: 0.568 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-baach14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.248 inches Body Length: 0.568 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bach144w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure: - Demilitarization: No Fig:	13.000 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65,0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.248 inches Body Length: 0.568 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 181205-baach14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: Na Unit Of Measure: - Demilitarization: No Fig:	Resistance Tolerance In Percent:
70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.248 inches Body Length: 0.568 inches Power Dissipation Rating In Watts: 1.000 fee air Style Designator: Axial terminal each end Test Data Document: 81 205-bacht14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-2.000/+2.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.248 inches Body Length: 0.566 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Tests Data Document: 81295-bach14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No Filg:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.248 inches Body Length: 0.568 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: V/a Unit Of Measure: Demilitarization: No Fiig:	70.0
Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.248 inches Body Length: 0.568 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: Na Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.248 inches Body Length: 0.568 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Shelf Life: Na Unit Of Measure: Demilitarization: No Filg:	150.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.248 inches Body Length: 0.568 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bach14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.248 inches Body Length: 0.588 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bacth14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	-65.0/+145.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.248 inches Body Length: 0.568 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.248 inches Body Length: 0.568 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.248 inches Body Length: 0.568 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Not established Body Diameter: 0.248 inches Body Length: 0.568 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Diameter: 0.248 inches Body Length: 0.568 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
0.248 inches Body Length: 0.568 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Length: 0.568 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
O.568 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.248 inches
Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
1.000 free air Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.568 inches
Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.000 free air
Test Data Document: 81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81205-bacrh14w specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0