Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-484-4999	
Section Quantity:	
1	
Body Style:	
Cylindrical	
Reliability Indicator:	
Not established	
Terminal Length:	
0.500 inches	
Body Diameter:	
0.310 inches	
Body Length:	
0.180 inches	
Actuator Type:	
Flush drive with slot-hole	
Effective Electrical Rotation In Deg Angular Rotation:	
280.0	
Center To Center Distance Between Terminals:	
0.200 inches	
Terminal Location:	
Rear end	
Mounting Method:	
Terminal	
Electrical Resistance Per Section:	
10.0 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
300.0	
Center To Center Distance Between Center Terminal And Outside Terminal:	
0.100 inches	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power	:
125.0 single section	
Power Dissipation Rating Per Section In Watts:	
0.5 free air single section	
Resistance Tolerance Per Section In Percent:	
-5.0 to 5.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 pin	

## NSN 5905-00-484-4999

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0