NSN 5905-00-484-5030

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-484-5030 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.688 inches **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.0935 inches **Shaft Length:** 0.688 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.000 inches **Overall Diameter:** 0.688 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Running Torque:** 2.00 inch-ounces **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing

10.0 kilohms single section

Rotary Actuator Travel In Angular Deg:
3600.0

Electrical Resistance Per Section:

NSN 5905-00-484-5030

Precision Wire Wound Variable Resistor - Page 2 of 2



Function Conformity Tolerance Per Section:

-1.00/+1.00 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0