Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-484-8036

## Section Quantity:

1

Body Style:

Rectangular bushing mounted

## **Reliability Indicator:**

Not established

## **Overall Length:**

1.645 inches

#### **Overall Height:**

0.406 inches

#### **Overall Width:**

0.266 inches

#### Shaft Diameter:

0.190 inches

#### Shaft Length:

0.270 inches

## Mounting Bushing Length:

0.375 inches

## **Body Length:**

1.344 inches

## Body Width:

0.266 inches

## **Body Height:**

0.312 inches

#### Shaft Style:

Round, slotted

## Shaft Bearing Type:

Bearing

## Actuator Type:

Single shaft

## Screw Thread Diameter:

0.190 inches

## Screw Thread Series Designator:

Unf

# Screw Thready Qty Per Inch (tpi):

32.0

## Terminal Location:

Rear end

## **Mounting Method:**

Standard bushing

## Features Provided:

Nonmetallic shaft

# NSN 5905-00-484-8036

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



**Electrical Resistance Per Section:** 10.0 kilohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0 to 100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0