## NSN 5905-00-485-2881

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-485-2881 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.094 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.625 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.969 inches **Undercut Diameter:** 0.125 inches **Shaft Style:** Round, stepped **Actuator Type:** Dual concentric **Effective Electrical Rotation In Deg Angular Rotation:** 315.0 **Undercut Length:** 0.750 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0

Terminal Location:
Radially positioned over less than half the circumference

Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
315.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections

## NSN 5905-00-485-2881

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
3.0 free air all sections
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No