NSN 5905-00-487-0482

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-487-0482

Section Quantity: Body Style: Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.360 inches **Body Length:** 0.275 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Maximum Starting Torque:** 7.50 inch-ounces **Maximum Running Torque:** 7.50 inch-ounces **Maximum Stop Torque:** 10.00 inch-ounces **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Hermetically sealed **Electrical Resistance Per Section:** 1.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 332.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.25 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

NSN 5905-00-487-0482

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig: A002a0