

NSN 5905-00-487-0758 Nonprecision Wire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-487-0758 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** Between 0.172 inches and 0.202 inches **Shaft Diameter:** Between 0.055 inches and 0.060 inches **Shaft Length:** 0.030 inches **Body Length:** Between 0.522 inches and 0.538 inches **Body Width:** Between 0.180 inches and 0.200 inches **Body Height:** Between 0.492 inches and 0.508 inches **Shaft Style:** Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

15120.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

Between 0.195 inches and 0.205 inches

Fragility Factor:

Moderately rugged

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal

Cubic Measure:

0.047 cubic inches

Electrical Resistance Per Section:

5.0 kilohms single section

NSN 5905-00-487-0758

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg: 15120.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** Between 0.095 inches and 0.105 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:** No