Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-487-8296

Section Quantity:

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

**Overall Length:** 

0.375 inches

Terminal Length:

0.188 inches

**Overall Height:** 

0.375 inches

Overall Width:

0.392 inches

Body Length:

0.375 inches

Body Width:

0.188 inches

Body Height:

0.375 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

240.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

0.10 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches

**Terminal Location:** 

Rear end

**Mounting Method:** 

Terminal

**Electrical Resistance Per Section:** 

1.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

360.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0 to 150.0 single section

## **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0