Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-488-7183

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Overall Length:**

1.957 inches

#### **Terminal Length:**

0.580 inches

Body Diameter:

1.680 inches

## Shaft Diameter:

0.250 inches

Shaft Length:

## 0.500 inches

## Mounting Bushing Length:

0.375 inches

**Body Length:** 

1.410 inches

# **Overall Diameter:**

2.260 inches

## Shaft Style:

Round, slotted

## Contact Arm Electrical Off Position:

Fully ccw

#### Actuator Type:

Single shaft

#### Maximum Starting Torque:

40.00 inch-ounces

#### Maximum Running Torque:

4.00 inch-ounces

#### Maximum Stop Torque:

240.00 inch-ounces

#### **Nonturn Device Location:**

At 12 oclock

# Nonturn Device Radius:

0.500 inches

# Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# NSN 5905-00-488-7183

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

**Electrical Resistance Per Section:** 

200.0 ohms single section

## **Rotary Actuator Travel In Angular Deg:**

290.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

Power Dissipation Rating Per Section In Watts:

25.0 heat sink single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

## Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

## Test Data Document:

81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

3 tab, solder lug

**Specification Data:** 

81349-mil-r-22/3 government specification

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A002a0