## NSN 5905-00-488-7226

**Section Quantity:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-488-7226

1
Body Style:
Rectangular w/bushing
Reliability Indicator:
Not established
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.700 inches
Body Width:
1.230 inches
Body Height:
1.335 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
312.0
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.530 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Lower adjacent side single row
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
51.100 ohms single section
Rotary Actuator Travel In Angular Deg:
312.0

## NSN 5905-00-488-7226

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A002a0