Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-489-2057

### Section Quantity:

1

Body Style:

Rectangular w/mounting holes

## Reliability Indicator:

Not established

#### **Overall Length:**

0.415 inches

#### **Terminal Length:**

0.300 inches

**Overall Height:** 

#### 0.375 inches

**Overall Width:** 

#### 0.503 inches

#### Mounting Hole Diameter:

## 0.074 inches

# Shaft Diameter:

# 0.090 inches

# Shaft Length:

0.040 inches

#### Body Length:

0.375 inches

#### Body Width:

0.203 inches

#### **Body Height:**

0.375 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

9000.0

## Maximum Starting Torque:

5.00 inch-ounces

## Maximum Running Torque:

5.00 inch-ounces

## Center To Center Distance Between Terminals:

0.200 inches

## Lateral Distance Between Mounting Hole Centers:

0.419 inches

## Mounting Facility Quantity:

2



Terminal Location:
Left adjacent side single row
Mounting Method:
Terminal and unthreaded hole
Electrical Resistance Per Section:
25.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0