

View Online at https://aerobasegroup.com/nsn/5905-00-489-2077

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Overall Length:**

2.281 inches

#### **Body Diameter:**

0.875 inches

### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.812 inches

#### Mounting Bushing Length:

# 0.250 inches

**Body Length:** 

1.469 inches

#### **Overall Diameter:**

1.250 inches

#### Shaft Style:

Round

#### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

3600.0

#### Maximum Starting Torque:

2.00 inch-ounces

#### Maximum Running Torque:

2.00 inch-ounces

#### Maximum Stop Torque:

60.00 inch-ounces

#### Shaft End Play:

0.015 inches

#### Shaft Radial Play:

0.005 inches

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0



Terminal Location:
Lower adjacent side single row
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
200.0 ohms single section
Rotary Actuator Travel In Angular Deg:
3625.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
otops
Function Characteristic Per Section:
-
Function Characteristic Per Section:
Function Characteristic Per Section: Single section linear
Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -0.0/+800.0 single section
Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -0.0/+800.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -0.0/+800.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section
Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -0.0/+800.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Terminal Type And Quantity:
Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -0.0/+800.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Terminal Type And Quantity: 3 solder stud
Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -0.0/+800.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Terminal Type And Quantity: 3 solder stud Shelf Life:
Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -0.0/+800.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Terminal Type And Quantity: 3 solder stud Shelf Life: N/a
Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -0.0/+800.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Terminal Type And Quantity: 3 solder stud Shelf Life: N/a
Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -0.0/+800.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Terminal Type And Quantity: 3 solder stud Shelf Life: N/a Unit Of Measure:
Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -0.0/+800.0 single section -0.0/+800.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Terminal Type And Quantity: 3 solder stud Shelf Life: N/a Unit Of Measure:  Demilitarization:
Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -0.0/+800.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Terminal Type And Quantity: 3 solder stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No